



27 615 KF2 EUPHORIA SYSTEM 260 SHOWER SYSTEM WITH SAFETY MIXER FOR WALL MOUNTING



PRODUCT DESCRIPTION

- Colour: phantom black
- consisting of:
 - horizontal swivable 450 mm shower arm
 - exposed Safety Mixer with Aquadimmer function
 - head shower Euphoria 260
 - spray patterns: Rain, SmartRain, Jet
 - maximum flow rate (at 3 bar): 7.5 l/min
 - with ball joint
 - hand shower Euphoria 110 Massage
 - maximum flow rate (at 3 bar): 8.5 l/min
 - adjustable in height with gliding element
 - shower hose Silverflex 1750 mm 1/2" x 1/2" (28 388)
 - maximum flow rate system (at 3 bar): 8.5 l/min
 - GROHE EcoJoy - less water, perfect flow
 - GROHE TurboStat - compact cartridge with wax thermoelement
 - GROHE SafeStop - safety button at 38°C
 - GROHE SafeStop Plus - optional temperature limiter at 43°C included
 - GROHE CoolTouch - no risk of scalding
 - GROHE ProGrip - with knurl structure
 - GROHE DreamSpray - perfect spray pattern
 - GROHE SprayDimmer - stepless flow rate adjustment
 - Flexible Installation - 1 adjustable bracket for existing drill holes
 - Inner WaterGuide - inner insulation for surface protection
 - GROHE SpeedClean - effortless limescale removal
 - TwistStop - to prevent hose from twisting
 - suitable for instantaneous heaters from 18 kW/h
 - minimum flow rate 5 l/min.
 - optional upgrade: GROHE EasyReach tray (26 362)
- professional edition